

Specifications

Feature	Description	
Product tanks	1300 or 1900L	
Rinse tank	150L	
Hand Wash tank	25L	
Hydraulics	Tractor remotes hydraulic quick connect fittings	Std
	Hydraulic hoses fitted with quick connect couplings	
	using tractor remote hydraulics for functions	Std
	If using hydraulic pumps, consideration to oil flow priority needs to be made to ensure consistent flow to pump while using other hydraulic function to limit motor RPM spike	Std
	If using hydraulic pumps, remote needs to have motor free spool mode to stop dead heading when turning off	Std
	Electric over hydraulic valve block and associated wiring	Opt
Chassis	Heavy duty fully welded mild steel RHS with intergrated fork lift pockets	Std
Paint	Grit blasted steel work followed by high build primer All welded sections seam sealed wet top coat paint system with low temperature baked finish	Std
Spray Pump	170 l/min, oil backed 4 diaphragm positive displacent	Std
Pump Drive	PTO pump drive	Std
	Hydraulic pump drive	Opt
Sprayer Control	Left hand side filling station	Std
Chemical handling & transfer	Chemical Suction Probe	Std
	23L height adjustable chemical induction hopper	Std
Control System	Raven SCS4400 auto rate controller and cabin harness	Std
	Pump speed sensor and magnet	Std
	High pulse flow meter	Std
	Wheel speed sensor kit and extension cable	Std
	Cabling to suit up to 8 boom section valves	Std
	ISOBUS control system	Opt

Feature	Description	
Filtration	1 x Suction with self-cleaning function	Std
	1 x Pressure	Std
Booms	Delta 3-way suspension boom in 12, 15, 18 & 24m	Std
	RHS Steel construction with truss style inner wings, cable fold and Aluminium outer wings	Std
	Hydraulic tower Lift & Fold	Std
	3/4" boom plumbing	Std
	Manual dual sided fence line nozzles	Std
Boom options	Individual hydraulic boom wing tilt	Opt
	Electric over hydraulic valve block and associated wiring	Std
	Single nozzles 500mm spacing	Opt
	Single nozzles 250mm spacing	
	Tri Jet nozzles 500mm spacing	Opt
	Tri Jet nozzles 250mm spacing	Std
	Boom Sections in 3, 5 or 7.	Std
	Broadacre or Rowcrop boom plumbing	Opt
	Electric dual sided fence line nozzles	Opt
	3D breakaway boom hinges	Opt
Gross weights (kg)	1300L	1650
	1900L	1950

*Weights based on no fluids in tank & 12m boom fitted.



LM 1300-1900

Full model details



The policy of Goldacres is one of continuous development and improvement. Goldacres reserve the right to alter any specifications, designs and prices of the range shown without notice and without incurring any obligation regarding such changes. The pictures and information shown or referred to in this publication are a general guide only. Should you purchase the items from this publication the publication does not form part of the contractual arrangements with Goldacres. The purchase of any item of equipment is subject to the Goldacres Terms and Conditions of sale. 02/25 - GA9500074



Ultimate spraying performance



Why choose LM sprayers?

- Australian engineering excellence
- Strong frame, single boom fold
- Maximum operator convenience
- Simple intuitive control



The Goldacres LM Three-Point Linkage Sprayer range represents the pinnacle of agricultural spraying technology.

Precision, performance, and durability, these sprayers are the ultimate solution for farmers demanding top-tier application capabilities.

Model Range

- Capacities: 1300L and 1900L
- Boom Options: 12m, 15m, 18m, and 24m Delta hydraulic fold booms
- Linkage Compatibility: Category 2 and 3, with quick hitch adapter support
- Frame: The frame incorporates fork lift legs for easy moving, made from RHS steel.



Delta boom

The Delta hydraulic lift and fold boom can be fitted in sizes 12, 15, 18 or 24m.

Control



Sprayer controls are clearly labelled, flip valves control all suction, pressure and filling functions.

A rotary valve enables suction from main product tank, rinse water tank and an external filling source eliminating the need for a dedicated fill pump.

A 23L height adjustable induction hopper is fitted for liquid or granular chemical.

Tank



A rotationally moulded UV stabilized polyethylene tank integrates a 150L rinse water tank for decontamination and a 25L hand wash tank for easy clean up.

Rate Control

Auto Rate control can be done with either Raven SCS4400 or ISOBus Section control with 3, 5 or 7 sections.

